



# PRESSERV

Making things last

# Utilisation of PIB Coating for long life protection of pipework and structural steel

Cost Efficient, Simple and Fast Corrosion Mitigation



[sealforlife.com](http://sealforlife.com)


# ICorr Aberdeen Webinar – PIB Based Coatings

Reducing the environmental footprint for surface preparation and coating

26<sup>th</sup> April, 2022


Presented by: Dinko Cudic and Stuart Rennie

# Selecting a coating system



Anti-corrosive but also UV resistance...

# Surface preparation and anchor profile




Roughness or anchor profile...



# Surface cleanliness



Chloride and surface contaminants...



ONE COMPANY INNOVATIVE TECHNOLOGIES ULTIMATE PROTECTION

# Atmospheric conditions

Ambient and surface temperature, humidity and dew point




Wind speed and coating thickness



Overspray...

# Equipment



**Heavy equipment backed by compressors...**

# Equipment

- Not easy to maintain the right angles




# Coating technique


- Maintaining thickness



- Workmanship is of essence



# Applicator safety




# Work environment



Courtesy of Total UK Limited

# Final inspection



# Effects of abrasive blasting

- Mining (garnet)
- Transport
- Storage and handling
- Safety hazard
- Waste creation
- Filtering
- Disposal




Figure 3: Comparison between potential hazards and existing control measures



# Effects of coating

- VOCs
- Heavy metals – lead, chromate
- Overspray
- Health
- Equipment cleaning
- Contaminated buckets
- Recycling energy
- Disposal



ONE COMPANY INNOVATIVE TECHNOLOGIES ULTIMATE PROTECTION

# Can it be as easy as this?

- Minimum surface preparation to St2 / St3



[sealforlife.com](http://sealforlife.com)

# Re defining corrosion prevention

Stopaq – or STOP AQUA

# Coating engineering requirements

- Minimum surface preparation requirement – St2
- No surface roughness required – dispersive adhesion mechanism
- Adheres to most surfaces, non coated or coated
- No corrosion under creep, impervious to oxygen and water
- Predefined coating thickness
- No VOCs, chemical exposure hours
- Harmless to the environment
- Emission free surface preparation and application contributor
- 30-year design life – compound does not dry / UV resistance / impact resistance
- Minimum waste management solution



ONE COMPANY INNOVATIVE TECHNOLOGIES ULTIMATE PROTECTION

# Approach



## Health, Safety, Environment and Sustainability



- Safety of people
  - No Hazardous components or chemicals used
  - No VOCs
  - Storage – non-flammable (no toxic fumes)
  - No hazardous equipment used for application



- Environmental impact
  - Nonhazardous materials
  - No emission equipment



- Economic aspect
  - Durability and lifetime performance design of minimum 30 years with zero maintenance intervals

# Polyisobutene


Designed to extend asset lifetime 30+ years

To stop corrosion

- Water, water vapor and gas impermeability
- Tacky even at low temperatures, both glass like and porous surfaces
- Creeps into pores and adheres at molecular level – dispersive
- High electrical resistance

To make is safe

- No smell, no evaporation of VOCs
- Skin irritant-free material
- Food industry approved
- Medical safe
- Kosher and Halaal



# The beginning

Compound pumped onto pipes

- Compound
- Netting
- Backing
- Mechanical protection




# The evolution

Bringing all the components into one in 1996



# Systems selection

Pipework



Structural





Paste, putty, filler



# Market Segmentation

One technology covering multiple applications

- Buried pipes and components
- Offshore / Onshore field joints
- Atmospheric
- Automated field applied systems (FAST)
- Corrosion Under Insulation
- Condensing Lines – wet substrate
- Splash Zone – submerged
- Insulation (sealing)
- Casing Filler
- Paintable - Basecoat
- Coating Repair Patch - pre pigmented solutions
- Sealing and waterproofing



Market segment	Standards	Solution	Items
Underground (buried)	ISO 21809-3	Wrappingband CZ, CZH, CZHT + Outerwrap + OGS (Optional)	Pipes and components
Offshore Field Joints (submerged)	ISO 21809-3	Wrappingband CZ, CZH, CZHT + Outerwrap + OGS (Optional)	Pipes and components
Atmospheric	ISO 12944	Wrappingband CZ, CZH, CZHT + Outerwrap + OGS (Optional)	Pipes and components
Atmospheric Coatable	ISO 12944	Wrappingband EZ, EZR / Basecoat H, HT + Topcoat	Structural
Atmospheric – pre pigmented	ISO 12944	SC coating repair patches	Structiral
Corrosion Under Insulation	ISO 19277	Wrappingband CZ, CZH, CZHT + Outerwrap	Pipes
Condensing Lines - UG/Atmospheric	ISO XXXX	Wrappingband CL + Outerwrap + OGS (Optional)	Pipes
Wet Substrate - Splash Zone	ISO 18797-2	Wrappingband SZ (WSH) + Intermediate + OGS Wrappingband CZ, CZH, CZHT + Outerwrap + OGS (Optional)	Piles and conductors (tubular objects)
Insulation & Cladding (sealing)	ISO 17738-1	Aluclad Insulwrap	Cladding seal - external Insulation seal
Corrosion prevention automated (FAST)	ISO 21809-1	Basecoat FAST + Polyurea / GRE / Outerwrap	Pipes, piles
Casing Filler	ISO 16440	Casing filler	Casings
Sealing and waterproofing	various	Aquastop 2100 Basecoat	Wall penetrations Roof, Internal lining

# Buried solutions

From compound to steel to a “wrap” applied coating

# Pipelines



Saudi Arabia – since year 2000

# Flanges



# Flanges and fittings

Wrappingband and putty used to smooth out bolted parts and smooth out the edges



# Pipe supports

Rigid, extra mechanical protection, used to distribute pin point pressure



# Offshore Field Joints

Offshore field joint application with reduced cycle times



# LNG / LPG storage tanks



# LNG storage tanks

Coatable backing and polyurea system withstanding extreme expansion and contraction coefficients



# Field applied automated system

Easy to assemble mobile coating unit on site for complete pipe coating



# Atmospheric solutions

From compound to steel to a “wrap” applied coating

# Stainless and duplex steel pipes




# Walkways

Minimum scaffolding and habitat requirement



# Conductor piles

Quick mobilisation and demobilisation accommodating to changing weather





# Sound dampening of “noisy” pipes

Reducing vibrations and creating a safer environment for the operators





# Flare booms

Minimum surface preparation requirements allow easy access



# Structures – offshore accommodation block

Reduction in operations allows quieter application where people sleep and work




# FPSO – flange encapsulation

Galvanic corrosion caused by use of stainless steel bolts on carbon steel flanges



# Stopaq CUI solution – Front End Engineering Design



# Under Insulation



# Application without shut-down



# Above Insulation

- InsulWrap
- AluClad

Sealing against rainfall  
and humidity



# EasyQote – WIND

Coating repair solutions



**Easy.Qote<sup>®</sup>**

# EasyQote product range in the Renewable Energy market

- EasyQote SC Patch grey and yellow
  - Atmospheric corrosion prevention and sealing solution
- EasyQote VE Paste
  - Mouldable material to fill up irregular shapes and sharp edges
- EasyQote VE Basecoat
  - Coatable corrosion prevention and sealing solution
- EasyQote WB Topcoat
  - Paint to be used over the EasyQote VE Basecoat




# EasyQote use on wind turbines







- Rotor shaft groove
- Internal coating repair Basecoat
- External coating repair SC Patch
- Ladder stubs
- Platform tower repair
- Flange sealant
- ICCP connection
- Sealing of voids in the TP
- Sealing of internal sensors
- ICCP Flanges
- Slip Joint

# Internal coating repair Basecoat




# Sealing of internal sensors



# External coating repair SC Patch



# SC Patches after more than 5 years in offshore condition



# Ladder stubs



# Flange sealant





2016.08.18

# Sealing of voids in the TP




# I CCP connection



# ICCP Flanges



# Slip Joint



# SC Patches on a sub stations



# Sandwich panel sealing



 **SEALFORLIFE**  
Industries



ONE COMPANY INNOVATIVE TECHNOLOGIES ULTIMATE PROTECTION

# Same application, different location: Electrical Wintrack towers

- EasyQote SC Patch as a sealant on a flanged connection





Self Adhering Coating Solutions

A wide-angle landscape photograph capturing a wind farm at sunset. The sky is a vibrant gradient of orange and yellow, with the sun low on the horizon. In the foreground, there is a vast field of red flowers, likely tulips, stretching across the frame. A row of wind turbines stands in the middle ground, their dark silhouettes contrasting against the bright sky. The overall scene conveys a sense of renewable energy and natural beauty.

One Company, Innovative Technologies, Ultimate Protection.


[sealforlife.com](http://sealforlife.com)

# Beyond Corrosion Prevention

Impact on HSE

# Surface preparation

## Minimum requirements



Cleanliness and adhesion check



No surface profile necessary

# Workplace set up




# Total cost of ownership

Evaluation of asset protection over time

- Evaluate performance of existing solutions, benefits / weakness
- Cost of solutions
- Cost of application / workmanship
- Cost of clean up / waste management
- Safety impact on applicators
- Waste management impact
- Emission (CO2) on environment
- Maintenance intervals
- Cost over time

Coating Vs Surface Preparation



# Client scheme evaluating Stopaq, 100m<sup>2</sup>



CRITERIA	BLAST & PAINT	STOPAQ	PERFORMANCE						
Waste	A stacked bar chart comparing waste volumes between two schemes. The 'BLAST & PAINT' scheme has a total waste of 2,000kg, composed of 150kg of 'Other' waste and 2150kg of 'General waste'. The 'STOPAQ' scheme has a total waste of 15kg. <table><tr><td>General waste</td><td>2,000kg</td></tr><tr><td>Other</td><td>150kg</td></tr><tr><td>Total</td><td>2150kg</td></tr></table>	General waste	2,000kg	Other	150kg	Total	2150kg	15kg	>99% Waste reduction
General waste	2,000kg								
Other	150kg								
Total	2150kg								
Carbon emissions	<ul style="list-style-type: none"><li>Sourced from beach or mining in India or Australia; requires 22,000km transport by bulk carrier</li><li>Special transport (separate A+B)</li></ul>	<ul style="list-style-type: none"><li>EU/Norwegian origin</li><li>Regular cargo</li></ul>	≥90% Reduced carbon emissions						
Safety	<ul style="list-style-type: none"><li>Hazard labeled</li><li>Flammable</li><li>Allergic reaction to skin due to high chemical exposure</li><li>Requires respirator mask given the dust content and exposure</li></ul>	<ul style="list-style-type: none"><li>VOC / CMR free</li><li>Non-flammable</li><li>No chemical exposure</li><li>No dust content nor exposure</li></ul>	Non-hazardous material and exposure						
Performance	<ul style="list-style-type: none"><li>10+ years maintenance interval</li><li>24 months shelf life</li><li>24-36 hours intervals between layers – system several days.</li></ul>	<ul style="list-style-type: none"><li>30+ years maintenance interval</li><li>Unlimited shelf life</li><li>Hot or cold applied</li><li>Complete system in same day</li></ul>	3X Extended maintenance interval						

## Conclusion:

Stopaq significantly minimizes the waste treatment and improve the environmental impact in project.

Stopaq represent a higher performance and also brings safety benefits for our operators.

# Cost comparison

## Atmospheric Wrap / CUI / Paintable VS. Industrial Coatings

Comparison Paint vs. Stopaq on pipes/bend 550m2 - actual project							
Abrasive blasting and 3 layer epoxy system	Amount	Rate/cost	Sum	Stopaq System CZH +PVC White	Amount	Rate/cost	Sum
Surface Preperation, Garnet blasting SA 2 <sup>1/2</sup>	1100 hours	50€	55000€	Surface Preperation, HP wash/isopropanol ST 2 <sup>1/2</sup>	410 hours	50€	20625€
Coating 3 layer epoxy system.	450L	8€	3600€	Stopaq CZ Stopaq PVC Outerwrap	2 layer system	100€	55000€
Rental equipment: HP wash, compressor, blasting pot, vacum unit, hoses, HP gun.	63 days	250€	12600€	Rental equipment: HP wash	10 days	50€	5000€
Consumables: Fuel, Garnet, HSEQ equipent.	Fuel 630L Garnet 11 tonn Misc.	6300€ 5500€ 1000€	12800€	Consumables: Misc and HSEQ equipent.	Misc	700€	700€
Application*	1100 hours	50€	55000€	Application	550 hours	50€	27500€
Waste consumption	11 tonn Garnet, Paint cans, brush, roll etc.	700€/tonn 50€	7750€	Waste consumption	Cartbord and foil	50€	50€
Personel	3-4 positions		68 days	Personel	2-3 positions		37 days
Personel accomodation, food and logistics.	4ea x 68 days	<u>200€</u>	54400€	Personel accomodation, food and logistics.	3ea x 37 days	<u>200€</u>	22200€
Sum:			<u>201150€</u>	Sum:			<u>131075€</u>

Does not include lifetime cost

# Thank You

